




Dept	
Qty	
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1


The information provided herein is from CONNPLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNPLY or its affiliates. Unauthorized use or reproduction of any part of this document is strictly prohibited. CONNPLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.



ACCESSORIES	X	Y
LONG LATCH	19.0	10.65
SHORT LATCH	17.5	8.0



P.C.B Layout (Tolerance:±0.05)
For Positions 10,26,30,34,50,70,90



P.C.B Layout (Tolerance:±0.05)
For Positions 20,40,60,68,80,100



(Series Image-Reference Only)


PINS PER ROW	A	B	C
5	24.50	5.08	11.46
10	30.85	11.43	17.81
13	34.66	15.24	21.26
15	37.20	17.78	24.16
17	39.74	20.32	26.70
20	43.55	24.13	30.51
25	49.90	30.48	36.86
30	56.25	36.83	43.21
34	61.33	41.91	48.29
35	62.60	43.18	49.56
40	68.95	49.53	55.91
45	75.30	55.88	62.26
50	81.65	62.23	68.61

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 04/10/08'		LJC 04/10/08'
B	DRAWING UPDATE	JLZ 08/22/18'		


NOTES:

- Materials
 - Contact: copper alloy
 - Insulation: Thermoplastic(UL94 V-0)
- Specification
 - Temperature:-40°C~+105°C
 - Contact Resistance:30mΩ max.(initial)
 - Insulation Resistance:1,000MΩ min
 - Dielectric Withstanding Voltage:AC 250V Per Minute

3.Product number code:



GENERAL TOLERANCE	ANGLE TOLERANCE	PROJECTION	TITLE
X. ±0.60	X. ±5°	UNITS mm	SHROUDED HEADER PITCH 1.27*2.54mm
.X ±0.38	.X ±3°	SHEET SIZE A4	SERIES DS1011-04 SERIES
.XX ±0.25	.XX ±2°		
DRAWING TYPE	CUSTOMER		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C-DS1011-04-XXXXXX-B		



晨翔电子有限公司
CONNPLY CONNPLY ELECTRONIC CO. LTD