






Dept	
Qty	
DC	1
ED	1
IE	1
ISO	1
PD	1
R&D	1
SD	1
QA	1
QC	1
QE	1

The information provided herein is from CONNELY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNELY or its affiliates. Unauthorized use or modification is strictly prohibited. CONNELY may enforce its intellectual property rights at its own discretion, failure or delays to exercise such rights does not constitute a waiver of such rights.



Recommend PCB layout
Tolerance: ±0.05



Circuit diagram



(Series Image-Reference Only)

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 05/09/18'		

NOTES:

- Specifications:
 - Contact Rating: 50mA at 12V DC
 - Insulation Resistance: 500MΩ min.
 - Contact Resistance: 100mΩ max.
 - Dielectric Withstanding Voltage: 250V AC(rms) for 1 minute.
 - Operating Life: 50,000 cycles
 - Travel: 0.25±0.1mm
 - Operation Temperature Range: -25°C to +70°C
 - Wave Soldering: Recommended Solder Temperature at 500°F(260°C)max. 5 Seconds
 - Hand Soldering: Use Soldering Iron Of 30 Watts, Controlled at 608°F(320°C) Approximately 2 Seconds.
- Product number code:

DS1042-15 - X X X X X X X

- Operating Life
05: 50,000 cycles
- Operating force
160: 160±50gf
250: 250±50gf
- Packing type
A: polybag
R: tape & reel
- Actuator color
W: White
- Housing color
B: Black
- Profile Height(DIM. H)
035: 3.5mm
- No. of contacts
3: 3Pos

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°
DRAWING TYPE		CUSTOMER	
SCALE		1:1	SHEET 1 OF 1
DRAWING NO.		C-DS1042-15-XXXXX-A	

PROJECTION		TITLE	TACT SWITCH SMT TYPE 4.5mmX3.28mm
UNITS	mm	SERIES	DS1042-15 SERIES

晨翔电子有限公司
CONNELY ELECTRONIC CO. LTD