



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	JLZ 01/28/15'		

- NOTES:
- Materials:
 - Housing material: LCP
 - Contact: Copper Alloy
 - Wire Insulator: PVC
 - Wire: Tin Plated Copper
 - Specifications:
 - Current Rating: 2A
 - Voltage Rating: 250V AC/DC
 - Contact Resistance: 20mΩ Max.(Connector Only)
 - Insulation resistance: 1000MΩ Min.(Connector Only)
 - Dielectric Withstanding Voltage: 800V AC(rms) For 1 Minute.
 - Temperature: -20°C~+130°C.
 - Product Number Code:

DS1137-13 - X X X X X X X

- PACKING TYPE
 - A: Polybag
 - R: Tape On Reel
 - T: Tray
- WIRE LENGTH(DIM L)(Male Only)
 - 050: 50mm
 - 180: 180mm
- HOUSING COLOR
 - W: White
- CONTACT PLATING
 - 6: Full Tin
 - 8: Full Gold
- MOUNTING TYPE
 - C: Crimp(Male Only)
 - S: SMT(Female Only)
- CONNECTOR TYPE
 - F: Female
 - M: Male
- No.OF CONTACTS
 - 2

Tel:86-574-63508787
 Fax:86-574-63510817
 E-mail:sale@connfly.com
 http://www.connfly.com
 Add:East Industry Zone KuangYan
 Town Cixi Ningbo Ch...
 P.C:315333

GENERAL TOLERANCE		ANGLE TOLERANCE	
X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

DRAWING TYPE	CUSTOMER
SCALE	1:1
SHEET	1 OF 1
DRAWING NO.	C-DS1137-13-XXXXXX-A

PROJECTION	TITLE
	3.2mm LED SERIDS CRIMP & FEMALE SMT TYPE CONNECTOR
UNITS	mm
SHEET SIZE	A4
SERIES	DS1137-13 SERIES

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO., LTD